

## Sentinel JetFlush Rapid®

### Effective, Easy Cleaning for Dirty Heating Systems

The Sentinel JetFlush Rapid unit is designed to be used in conjunction with the Sentinel range of chemical cleaning products for the safe and easy removal of the sludge and debris from central heating systems.

- **High flow rate and reversible flow**  
Enables rapid and effective removal of debris, quickly helping to restore optimum system efficiency
- **Lightweight and compact with ergonomic design**  
Easy to handle and operate; ideal for small properties and flats
- **Complete with easy-to-use hoses and fittings**  
Allows unit to be easily and quickly connected anywhere on the system
- **Integral fresh water flush facility**  
Allows direct flush of all debris to waste and not returned to the system

**17kg**  
Total weight  
17kg

**Dimensions**  
Height: 690mm  
Width: 390mm

**90l/min**  
Flow rate  
90 litres  
per minute

**Instantaneous  
flow  
reversal**



### The Sentinel System

Lifetime protection for heating and hot water systems using the best practice process of...



**CLEAN**  
WITH  
APPROPRIATE  
CLEANER



**PROTECT**  
WITH X100  
INHIBITOR



**MAINTAIN**  
WITH  
TEST KIT

## Additional Features

- Instant Flow reversal
- Integral fresh water flush capacity
- Complete with hoses and fittings
- Self-priming for ease and safety
- High flow rate for maximum cleaning
- Reversible dumping facility
- Rapid removal of system debris
- Ergonomic design

## Technical Specification

<b>Material of Construction</b>	HD polyethylene tank
<b>Tank Capacity</b>	39 litres
<b>Dimensions</b>	Height: 69cm/Width:39cm/Depth:44cm
<b>Weight</b>	Empty: 17kg. Full:56kg
<b>Power Requirements</b>	230V, 50Hz single phase motor, Nominal rating: 3.0 amperes, Schuko plug
<b>Pressure Rating</b>	Recirculating: 10psi, Against closed valve: 22psi
<b>Flow Rate</b>	Recirculation: 90l/min maximum
<b>Hose</b>	2x5m, 16mm I.D flow and return hoses 1x8m, 16mm I.D discharge hose 1x3m overflow hose
<b>Physical Limitations</b>	Maximum temperature range: 75°C

The use of Sentinel water treatment is endorsed by the industry's major international manufacturing companies\*

           

### Sentinel Performance Solutions Ltd

7650 Daresbury Park, Warrington, Cheshire, WA4 4BS, United Kingdom.

Tel: +44 (0)1928 704 330 [www.sentinelprotects.com](http://www.sentinelprotects.com)



@SentinelHQ



SentinelCPM